

## SHANGRAO RUICHEN SEALING CO.,LTD DONGGUAN RUICHEN SEALING CO.,LTD

Address: Road 8.Yanshan Industrial Estate, Shangrao City, 334500, Jiangxi Prov., CHINA Tel: +86-18024335478 E-mail: aaron@dgork.com

	TEST REPORT			
FKM70 BLACK FDA (V7001F) COMPOUND       ASTM D2000 M2HK 710 A1-10 B38 E078 EF31 F13				
Sheet : 10min 170℃ Button : 10 min 170℃				
	ORIGINAL PROPERTIES	SPECIFICATION	TEST RESULT	ASTM TEST METHO
HARDNESS SHORE A	70°±5	71	D2240	
TENSILE STRENGTH, MPA, MIN	≥10	11.98	D412	
ULTIMATE ELONGATION, %, MIN	≥175	231.58	D412	
SPECIFIC GRAVITY (g/cm <sup>3</sup> )		1.95	D297	
HEAT RESISTANCE 70 H . AT 250 °C (A1-10)			D573	
CHANGE IN HARDNESS, POINTS	+10	+2		
CHANGE IN TENSILES STRENGTH, %	-25	+5.59		
CHANGE IN ULTIMATE ELONGATION,MAX %	-25	-12.39		
COMPRESSION SET, MAX, 22H AT 200 °C (B38)	≤30	14.93	D395	
FLUID RESISTANCE FUEL.101. 70H AT 200 $^\circ\!$			D471	
CHANGE IN HARDNESS, POINTS	-15~+5	-10		
CHANGE IN TENSILES STRENGTH, MAX %	-40	-19.8		
CHANGE IN ULTIMATE ELONGATION, MAX %	-20	-10.29		
CHANGE IN VOLUME %	0~+15	+10.82		
FLUID RESISTANCE FUEL C, 70H AT 23°C (EF31)			D471	
CHANGE IN HARDNESS, POINTS	±5	-2		
CHANGE IN TENSILES STRENGTH, MAX %	-25	-15.2		
CHANGE IN ULTIMATE ELONGATION, MAX %	-20	-13.8		
CHANGE IN VOLUME %	0~+10	+5.2		
LOW-TEMPERATURE BRITTLENESS NONBRITTLE				

the same results can be obtained other laboratories, using different conditions by the preparation and
evaluation of the samples.

Approved By Frankie Fang Checked By: Y	Yunli Tu Tested By:	Jianjun Zhu
--	---------------------	-------------